

编号	内孔	内孔公差	内台阶	内台阶公差	外径	外径公差	对边	对边公差	高度	高度公差	齿数	材质	油品	备注
5-104	2	+0.012 ⁺ +0.004	-		4.1		-		5.4	+0.1	-	C-01	C68	R头
5-105	3	+0.001 ⁺ -0.002	3.1		5.5		-		10	+0.15	6	QMP-1	PSL-19	
5-138	4.8	+0.05 ⁺ +0.03	-		-		9.55	+0.02	9.4	+0.1	-	C-05M	BL-1#	六棱
5-138-3	4.8	+0.05 ⁺ +0.03	-		-		9.55	+0.02	9.4	+0.1	-	QMP-1	78/947P	六棱
5-140	5	+0 ⁺ -0.2	-		-		7	+0 ⁺ -0.02	7	+0.02	-	QMP-1	626	六棱
5-148	6.4	+0 ⁺ -0.02	-		11	01	9	+0.05 ⁺ +0	9	+0.05	-	C-02C	#685-M	扁方
5-150-3	8.1	+0 ⁺ -0.1	-		-		11.8	+0 ⁺ -0.1	18.5	+0.2	-	C-02N	FDA-1	六棱
5-150-4	8.1	+0 ⁺ -0.1	-		-		11.8	+0 ⁺ -0.1	18.5	+0.2	-	C-08	FDA-1	六棱
5-155-2	5	+0.013 ⁺ +0.007	-		14	+0.03	11.5	+0 ⁺ -0.01	7	+0.1	-	FCU30W	ST#32B	
5-160-2	2	-0.002 ⁺ -0.006	2.08		4	+0.01 ⁺ +0	-		4.3	+0.1	-	H-02	OIL 947	中空, 两头内孔不一致
5-163	6.4	+0 ⁺ -0.02	-		11	01	9	+0.05 ⁺ +0	10	+0.05	-	C-02C	FDA-1	
5-163-2	6.4	+0 ⁺ -0.02	-		11	01	9	+0.05 ⁺ +0	10	+0.05	-	C-02C	#685-M	
5-163-3	6.4	-0.03 ⁺ -0.04	-		11	01	9	+0.10 ⁺ +0.05	10	+0.05	-	C-02C	#685-M	内倒角C0.2, 外倒角C0.9
5-163-3	6.4	-0.03 ⁺ -0.04	-		11	01	9	+0.10 ⁺ +0.05	9	+0.05	-	C-02C	#685-M	
5-163-4	6.4	-0.03 ⁺ -0.04	-		11	01	9	+0.10 ⁺ +0.05	10	+0.05	-	C-02C	#685-M	内倒角C0.3, 外倒角C0.5
5-169	3.15	+0.005 ⁺ +0	-		7	+0 ⁺ -0.025	-		10	+0.1	24	FC-10	-	
5-172	2	+0.004 ⁺ -0.005	2.24	+0.1 ⁺ +0	5	+0 ⁺ -0.1	3.4	+0.05	11	+0.1	-	AC15	-	4.3大扁方
5-173	2	+0.004 ⁺ -0.005	2.24	+0.1 ⁺ +0	5	+0 ⁺ -0.1	3.4	+0.05	11	+0.1	-	AC15	发黑	4.3大扁方
5-173-2	2	+0.005-0.008	2.24	+0.1 ⁺ +0	5	+0 ⁺ -0.1	3.4	+0.05	11	+0.1	-	FC-06A	发黑	4.3大扁方
5-175	4	+0.008 ⁺ +0.004	-		9	+0.02 ⁺ +0	8.5	+0 ⁺ -0.15	4	+0.05	-	FCU30W	ST#68B	
5-177	1.1	+0.05	-		6	+0.1 ⁺ +0	-		3.6	+0.05	-	AC15	ST#68B	盲孔
5-177-2	1.1	+0.05	-		6	+0.1 ⁺ +0	-		3.6	+0.05	-	AC15	#630	盲孔
5-186	3	-0.02 ⁺ -0.05	-		7.1	+0.06 ⁺ +0	-		4	+0.05	10	AC15	-	
5-197	8.5	+0.02	-		22	+0.02	21	+0 ⁺ -0.1	3	+0 ⁺ -0.1	-	C-04X	T68	
5-216	1.98	+0 ⁺ -0.02	-	盲孔	5.6	+0.05	-		6	+0.1	6	AC15	过防锈油	单头带齿
5-219	6.4	-0.03 ⁺ -0.04	-		11	01	9	+0.10 ⁺ +0.05	11.5	+0.05	-	C-02C	#685M	
5-225	1.8	-0.005 ⁺ -0.025	-		5.8	+0 ⁺ -0.05	-		4	+0 ⁺ -0.1	12	CFY-116	AC18	
5-227	9	+0.06 ⁺ +0.03	-		13	.029	7.3	+0.07 ⁺ +0.01	10	+0.1	-	AC17	T68	内孔扁方
5-233	1.5	+0.01 ⁺ +0	-	盲孔	6	05	-		7	+0.05	36	QMP-1	G-26	
5-234	0		-		4	+0 ⁺ -0.05	-		1.2	+0.05	-	QMP-1	G-26	
5-242	8	+0.02 ⁺ +0	-		14	+0.1	7.2	+0.02 ⁺ +0	12	+0.05	10	AC15	T11处理	内孔扁方
5-242-2	8	+0.02 ⁺ +0	-		14	+0.1	7.2	+0.02 ⁺ +0	12	+0.05	10	AC15	T11处理	内孔扁方, 单面环槽
5-248	5	+0.01	-		10	+0.1	9	+0.01	16.75	+0.1	-	C-01	FG100	
5-249	5	+0.02	-		10	+0.1	9	+0.01	14	+0.1	-	C-01	FG100	

5-253	2	+0.025+0.015	-		3.5	005	-		3	+/-0.05	1	C-01	WS-P24	
5-255	3.2	+0.05+0	-	盲孔	16	+/-0.2	10	+/-0.2	12	+/-0.2	-	F-01	防锈油	机加斜孔2.6*14°
5-256	3.2	+0.05+0	-	盲孔	16	+/-0.2	10	+/-0.2	12	+/-0.2	-	F-01	防锈油	机加斜孔2.6*12.5°

编号	内孔	内孔公差	外径	外径公差	偏心距	偏心距公差	高度	高度公差	材质	油品	备注
5-179	1.5	-0.01 ^{^-} -0.03	5.8	±0.05	1.25	±0.05	4.5	±0.1	F-40N	过T68油	凸轮
5-179-2	1.5	-0.01 ^{^-} -0.03	5.8	±0.05	1.25	±0.05	4.5	±0.1	F-01	过T68油	凸轮
5-181	1.5	+0.02 [^] +0	6.1	±0.05	1.65		4	±0.1	F-40N	-	
5-183	1.5	+0.02 [^] +0	6.1	±0.05	1.65		8	±0.1	F-40N	-	
5-204	1.5	+0.02 [^] +0	6.1	+0.05 [^] +0	1.5	+0.02 [^] +0	5.5	±0.1	F-40N	过防锈油	
5-205	1.5	+0.03 [^] +0	6	±0.05	1.5	±0.05	6	±0.1	F-01	过防锈油	
5-206	1.5	+0.03 [^] +0	6	±0.05	1.5	±0.05	5.5	±0.1	F-01	过防锈油	
5-206-2	1.5	-0.010 ^{^-} -0.035	6	±0.05	1.5	±0.05	5.5	±0.1	F-01	T68	
5-207	1.5	+0.025 [^] +0	7	±0.05	1.25	±0.05	5	±0.1	F-01	过防锈油	
5-207-2	1.5	-0.010 ^{^-} -0.035	7	±0.05	1.25	±0.05	5	±0.1	F-01	过防锈油	
5-208	1.5	+0.025 [^] +0	5.8	±0.05	1.3	±0.05	4.5	±0.1	F-01	过防锈油	
5-208-2	1.5	-0.010 ^{^-} -0.035	5.8	±0.05	1.3	±0.05	4.5	±0.1	F-01	过防锈油	
5-209	1	+0.025 [^] +0	5	±0.05	1.25	±0.05	5	±0.1	F-01	过防锈油	
5-210	1	+0.025 [^] +0	6	±0.05	1.5	±0.05	4	±0.1	F-01	过防锈油	
5-210-2	1	+0.025 [^] +0	6	±0.05	1.5	±0.05	4	±0.1	F-01	-	
5-210-3	1	-0.015-0.040	6	±0.05	1.5	±0.05	4	±0.1	F-01	过防锈油	
5-211	1	+0.025 [^] +0	6	±0.05	1.5	±0.05	4.5	±0.1	F-01	过防锈油	
5-213	1.5	+0.03 [^] +0	6	±0.05	1.5	±0.05	4	±0.1	F-01	过防锈油	
5-213-2	1.5	-0.010 ^{^-} -0.035	6	±0.05	1.5	±0.05	4	±0.1	F-01	过防锈油	
5-214	1.5	+0.025 [^] +0	7	±0.05	1.25	±0.05	4	±0.1	F-01	过防锈油	
5-214-2	1.5	-0.010 ^{^-} -0.035	7	±0.05	1.25	±0.05	4	±0.1	F-01	过防锈油	
5-215	1.5	+0.025 [^] +0	7	±0.05	1.25	±0.05	6.5	±0.1	F-01	过防锈油	
5-217	1.5	+0.025 [^] +0	7	±0.05	1.25	±0.05	7	±0.1	F-01	过防锈油	
5-218	1.5	+0.030+0	6	±0.05	1.5	±0.05	4.5	±0.1	F-01	过防锈油	
5-218-2	1.5	-0.010 ^{^-} -0.035	6	±0.05	1.5	±0.05	4.5	±0.1	F-01	过防锈油	
5-222	1	+0.025 [^] +0	6	±0.05	1.5	±0.05	5.5	±0.1	F-01	过防锈油	
5-228	1	+0.03 [^] +0	6	±0.05	1.5	±0.05	6	±0.1	F-01	过防锈油	
5-229	1	+0.025 [^] +0	6	±0.05	1.5	±0.05	5.5	±0.1	F-01	过防锈油	
5-231	1.5	+0.025 [^] +0	7	±0.05	1.25	±0.05	4.3	±0.1	F-01	过防锈油	

5-238	1	+0.025 ⁺ 0	7	+-0.05	1.5		6	+-0.1	F-01	-	
5-238-2	1	-0.010-0.035	7	+-0.05	1.5		6	+-0.1	F-01	过防锈油	
5-239	1	+0.03 ⁺ 0	13	扇形	0		6.1	+-0.1	F-01	过防锈油	
5-240	1	+0.025 ⁺ 0	7	+-0.05	1.5		5	+-0.1	F-01	过防锈油	
5-240-2	1	-0.010-0.035	7	+-0.05	1.5		5	+-0.1	F-01	过防锈油	
5-243	1	+0.025 ⁺ 0	7	+-0.05	1.5		4	+-0.1	F-01	-	
5-245	1.5	+0.03+0	10.6	1/4圆	0.2		7.2	+-0.1	AC17	过防锈油	
5-246	2	+0.04+0.01	22	扇形	0		8.2	+-0.1	AC15	过防锈油	
5-246-2	2		22	扇形	0		8.2	+-0.1	AC15	过防锈油	锥度内孔
5-264	1.5	+0.03+0	6	+-0.05	1.5	+-0.05	8	+-0.1	AC15	过防锈油	
5-265	2	+0.04+0.01	22	扇形	0		5	+-0.1	AC15	过防锈油	
5-266	1	+0.025+0	5	+-0.05	1.25	+-0.05	7	+-0.1	F-01	过防锈油	